



### RT • 2 poli

	Portata <i>Airflow</i>																		Qv m <sup>3</sup> /h	
	kW	gr.	1000	1250	1500	1750	2000	2250	2500	2750	3000	3250	3500	3750	4000	4500	5000	5600		
RT 252	0,18	63	180	170	148	120	75	25	10											
RT 302	0,7	71					256	220	198	175	148	123	75	20						
RT 352	0,55	71										250	235	210	195	148	85	10		

P. Stat.  
Pa

### RT • 4 poli

	Portata <i>Airflow</i>																		Qv m <sup>3</sup> /h	
	kW	gr.	500	1000	1500	2000	2500	3000	4000	5000	6000	7000	8000	9000	10000	11000	12000	13000		
RT 254	0,09	56	44	20	12															
RT 304	0,09	56			72	23	5													
RT 354	0,13	63				87	55	10												
RT 404	0,18	63					115	98	50	12										
RT 454	0,25	71						125	114	78	25									
RT 504	0,37	71							148	125	110	68	7							
RT 554	0,55	80							175	163	148	125	98	55	10					
RT 604	0,75	80									205	188	177	154	125	97	48	12		

P. Stat.  
Pa

### RT • 6 poli

	Portata <i>Airflow</i>																		Qv m <sup>3</sup> /h	
	kW	gr.	1500	1750	2000	2500	3000	3500	4000	4500	5000	5500	6000	6500	7000	8000	9000	10000		
RT 406	0,12	63	50	42	40	27	5													
RT 456	0,12	63		58	55	48	42	26	12											
RT 506	0,18	71				64	60	57	51	43	32	18	10							
RT 556	0,18	71							68	61	55	48	37	26	12					
RT 606	0,37	80									88	84	80	74	70	52	28	10		

P. Stat.  
Pa